

GANTRY MILLING MACHINE

# FRFQ 200-VR/A6

SPECIAL OFFER



# FRFQ 200-VR/A6

## PARAMETRES

<b>Technical parameters of machine</b>	FRFQ 200-VR/A6
<b>Axis Y, cross</b>	2 800 mm, 30 000 mm/min
<b>Axis X, longitudinal</b>	6 000 + 1 000 for heads exchange, 30 000 mm/min
<b>Axis Z, vertical, headstock</b>	Shift-out 1 500 mm – 6 000 rpm, p = 45 kW, 20 000 mm/min
<b>Table</b>	2 000 x 6 000 mm
<b>Milling head 1</b>	VK – two axis continuous head - spindle BT50
<b>Milling head 2</b>	VA1 – straight head - spindle BT50
<b>Milling head 3</b>	VP1 – angular head - spindle BT50
<b>Milling head magazine</b>	fixed for 3 milling heads
<b>Cooling system</b>	NT 1 500 l – 5 bar; VT 150 l – 20 bar
<b>Chain type tool magazine</b>	R40 - BT50, HT8
<b>Control system</b>	Siemens S840DSL
<b>Probe</b>	Renishaw RMP 60
<b>Control panel</b>	15", hand weel HT2
<b>Chip conveyers</b>	2 x chain-type conveyors + container
<b>Machine colour</b>	RAL 7035 + RAL 7021, RAL 3020
<b>Date of delivery (acceptance in TOS KUŘIM)</b>	immediately